

**PRODUCT DATA**

Product Name	HYPER REV TUNE 5W-50	HYPER REV TUNE 0W-20	RACING HYPER 10W-60	RACING TURBO 10W-50	RACING NA-V 5W-40	RALLI ART Engine OIL 5W-45	RACING NA 0W-40	RACING NA 0W-30	Version-S 5W-40	Version-S 5W-30	Inspection Method	
SAE Grade	10W-60	0W-20	10W-60	10W-50	5W-40	5W-45	0W-40	0W-30	5W-40	5W-30	-	
Density (15°C) g/cm3	0.8837	0.8696	0.8750	0.8764	0.8693	0.8699	0.8656	0.8655	0.8458	0.8440	JIS K 2249-1	
Colour ASTM	L3.0	L2.5	L3.0	L2.5	L2.5	L3.0	L2.5	L2.5	L3.5	L3.0	JIS K 2580	
Flash Point (COC) °C	226	228	248	248	240	246	230	238	248	244	JIS K 2265-4	
Viscosity	40°C mm <sup>2</sup> /s	110.9	44.15	167.1	108.5	93.26	96.60	82.24	60.79	77.45	63.25	JIS K 2283
	100°C mm <sup>2</sup> /s	18.24	8.462	24.32	17.93	15.90	16.47	14.29	10.88	13.15	10.83	JIS K 2283
Viscosity Index	183	172	178	183	183	185	181	172	172	163	JIS K 2283	
CCS (-25°C) mPa·s	4720	3890	6440	3070	3770	3960	6190	5580	3200	3410	ASTM D5293	
Pour Point °C	-30	-50	-45.0	-42.5	-47.5	-47.5	-42.5	-42.5	-50.0	-47.5	JIS K 2269	
Acid Value mgKOH/g	4.1	3.8	1.94	2.56	3.54	4.35	4.26	3.82	2.10	2.03	JIS K 2501	
TBN mgKOH/g	8.35	8.4	8.47	8.75	8.10	8.47	8.50	8.15	7.70	7.59	JIS K 2501	